M 112 500 NDP AK







- Self powered monitor
- High quality finish in standard version
- Flat amplitude and phase response
- Integrated flying system
- Smooth design

Application

- Concert monitor
- PA system
- Zone sound system













M 112 NDP AK is a self-powered stage monitor with 500 W output power. Construction design allows to use the model as a wedge on the stage as well as on a speaker stand or rigged with flying points. Enclosure is finished with Poliurea – highly resistant material. Integrated power amplifier module allows signal connection from microphone or line.

Frequency range	50 Hz-20 kHz
Output power	500 W
SPL (1W / 1m)	99 dB
Components	LF: 12" / 2,5" ND HF: 1"/1"
Finish	Poliurea, steel grill
Dimensions(HxWxD) [mm]	605 x 378 x 365
Weight	16,5 kg
Connectors	Input: XLR, Jack 6,4mm, RCA Stereo Link: XLR
EQ	Seperate Hi/Mid/Low
Monitoring	LED: Ready / Limiter
Optional output	Speakon Out (minimum 8Ω)
Power supply	Shuko-IEC 230V/50Hz
Optional accessories	
Flying system	PA RIG 002
Cover	COVER M112NDPAK

Enclosure is made of durable high grade plywood with integrated flying points and adjustable angle speaker stand socket pole.

Input signal can be connected via XLR, RCA or Jack connectors. Simple band equalizer allows adjustment of output with three separate potentiometers for High, Mid and Low part of bandwidth.

Advanced crossover was designed with highest attention to details. Outcome of this is flat amplitude and phase response.

Accessories

- PA RIG 002
- COVER M112NDPAK
- PA STAND 001

System Components

■ POL-AUDIO TV 118

