

## MP 115 CX ND



MP 115 CX ND is a two way passive stage monitor with 15" coaxial transducer with 1" high frequency unit with a passive crossover. Horn attached at high frequency exit provides stable coverage of 80° (vertically) on 60° (horizontally). Transducer project makes the enclosure smaller and lighter. Coaxial placement of transducers acts like a single point source providing coherent wave front.

## Main features

- Professional stage monitor
- Quality finish in standard version
- Flat amplitude and phase response
- Integrated suspension system
- Smooth design
- Coaxial speaker

## Application

- Medium to large scale events
- Demanding artists
- Live events

<b>Frequency range</b>	50 Hz-20 kHz
<b>AES Power</b>	500 W
<b>Program power</b>	1000 W
<b>SPL (1 W/1 m)</b>	98 dB
<b>Components</b>	LF: 15" / 3" HF: 1,75"
<b>Impedance</b>	8Ω
<b>Enclosure</b>	Sklejka bałtycka
<b>Finish</b>	Obudowa pokryta farbą, przód osłonięty stalową maskownicą oraz gąbką dźwiękoprzuszczalną
<b>Dimensions (HxWxD) [mm]</b>	365 x 590 x 535
<b>Weight</b>	19 kg
<b>Suspension</b>	Punkty montażowe do uchwytów na łańcuch
<b>Dispersion</b>	H 60° V 80°
<b>Optional accessories</b>	
<b>Flying kit</b>	PA RIG 002
<b>Enclosure cover</b>	Standard black as an option can be covered with any color from RAL

Cabinet is made of high quality plywood and is covered with Poliurea – highly impact resistance material. Front of the system is covered with steel grill and acoustic foam. Integrated rigging points and speaker stand socket pole with adjustable angle makes the system not only a top class wedge but also extremely versatile loudspeaker system for rental companies.

Crossover was design with utmost attention to details, delivering flat amplitude and phase response. Smooth design and extremely high sonic performance makes MP 115 CX ND a perfect tool for heavy duty stage applications.

## Accessories

- PA RIG 001
- COVER MP115
- PA STAND 001

## System Components

- POL-AUDIO TP 118